WHAT ARE THE DIFFERENT TYPES OF CONTROL VALVES?

07/20/25 05:31:00 PM



1. Introduction

Control valves are the final control elements in automated process loops, modulating fluid flow, pressure, temperature, or level by varying the flow passage in response to a control signal from a controller.

Selecting the appropriate control valve type, actuator, and flow characteristic is critical to achieving precise regulation, system stability, and operational safety.

2. Classification Criteria

2.1 Motion of the Closure Member

- Linear motion valves: closure member moves perpendicular to flow (e.g., globe, gate, diaphragm, pinch)
- Rotary motion valves: closure member rotates about an axis (e.g., ball, butterfly, plug)

2.2 Actuator Action

- Air-to-Open (ATO): pneumatic signal drives valve open; loss of air closes valve
- Air-to-Close (ATC): pneumatic signal drives valve closed; loss of air opens valve These fail-safe positions are chosen based on safety requirements (e.g., steam shut-off or emergency cooling)

2.3 Number of Seats (Plugs)

- Single-seated valves: one disk/plug; can achieve 0–100% flow and tight shut-off
- Double-seated valves: two plugs balance thrust forces, reducing actuator size but cannot fully seal to zero due to differential thermal expansion

2.4 Flow Characteristics

- Linear: flow change is proportional to stem lift
- Equal percentage: each incremental lift produces the same percentage change in flow
- Quick opening: large flow change at small lifts Inherent characteristics describe valve-only behavior; installed (effective) characteristics account for piping and pressure conditions

3. Core Valve Types

3.1 Globe Valves

Globe valves feature a linear plug moving against a fixed seat within a spherical or “globe” body. They provide excellent throttling control and predictable flow characteristics but impose a higher pressure drop due to their tortuous flow path. Typical applications include steam control, feedwater regulation, and precise process throttling.

3.2 Gate Valves

Gate valves employ a sliding gate that fully opens or closes the passage. In the fully open position they offer minimal resistance and very low pressure drop, making them ideal for on/off service. They are unsuitable for throttling, as partial opening can cause gate and seat damage.

3.3 Ball Valves

Ball valves use a quarter-turn hollow ball to control flow. They deliver tight shut-off with low pressure drop and fast operation. While standard ball valves are mainly on/off devices, specialized V-port and multi-port designs enable modest throttling. Common in chemical, petrochemical, and gas applications.

3.4 Butterfly Valves

Butterfly valves consist of a disc mounted on a central shaft, rotating 90° from open to closed. They are lightweight, compact, and handle large flow capacities. Due to seat leakage when partially open, they are rarely used for precise throttling but excel in HVAC, water distribution, and large-diameter pipelines.

3.5 Diaphragm Valves

Diaphragm valves feature a flexible elastomeric diaphragm that presses against a weir or seat. They have no stem packing, eliminating leakage paths, and are excellent for corrosive, abrasive, or slurry services. Pressure and temperature limits are lower than metal-seated valves, restricting them to mild process conditions.

3.6 Pinch Valves

Pinch valves use an elastomer sleeve that is “pinched” closed by an external mechanism. The sleeve isolates the media entirely, making these valves ideal for slurries, solids-laden fluids, and corrosive compounds. Their unobstructed flow path results in very low pressure drop under open conditions.

3.7 Needle Valves

Needle valves have a tapered needle-shaped plunger that enters a matching seat. They afford very fine flow control at low flow rates and are commonly used in instrumentation, sampling lines, and low-pressure gas circuits.

3.8 Plug Valves

Plug valves contain a cylindrical or conical plug with a lateral passage. Rotating the plug aligns or blocks the passage to open or close flow. Simple in construction and quick to actuate, they tolerate abrasive media and high temperatures but lack the precise throttling of globe valves.

3.9 Specialty and Multi-Way Valves

- Three-way (mixing/diverting) valves: direct flow between two outlets or mix two inlets
- Pressure-reducing and back-pressure valves: maintain set downstream or upstream pressure
- Safety (relief) valves: automatically open at over-pressure to protect equipment
- Cryogenic and sanitary designs: constructed for extreme temperatures or hygienic standards

4. Valve Trim and Internal Components

Valve trim refers to the internal components—plug, seat, cage, stem, and guiding hardware—responsible for flow control, leakage performance, and erosion resistance. Common trim styles include cage, V-notch, multi-hole, and balanced plug designs. Proper trim selection optimizes rangeability, reduces noise, and minimizes cavitation risk.

5. Actuator Types

Control valves are paired with actuators that convert control signals into mechanical motion:

- Pneumatic actuators: use air springs or diaphragms; fast response and inherent fail-safe action; most widely used in process industries
- Electric actuators: motor-driven; high positioning accuracy and easy digital integration but slower and more expensive than pneumatic systems
- Hydraulic actuators: employ incompressible fluid; deliver large forces for heavy or high-pressure valves; require hydraulic power units and more maintenance
- Electro-hydraulic actuators: combine the precision of electric drives with hydraulic power for high-force, accurate control

6. Flow Characteristic Implementation

The inherent flow characteristic is determined by the plug shape. When installed, piping geometry and pressure conditions alter it to the effective characteristic experienced in service. Equal-percentage plugs are preferred for wide turndowns, while linear plugs suit accurate proportional control over narrow ranges. Quick-opening plugs provide fast on/off action but poor modulation.

7. Selection and Sizing Considerations

Key factors in valve selection and sizing include:

- Required flow coefficient (Cv) and pressure drop
- Process fluid properties (corrosiveness, viscosity, solid content)
- Operating pressure and temperature conditions
- Shut-off class and leakage requirements per ANSI/IEC standards
- Actuator fail-safe requirement and available power source
- Material compatibility and inspection/maintenance needs

Calculation of Cv and selection of trim/material must adhere to ISA and API sizing procedures to ensure performance and longevity.

8. P&ID Symbols and Identification

Standardized symbols (ISO 10628, ANSI/ISA-5.1) distinguish valve types and actuation on Piping & Instrumentation Diagrams:

- Globe valve: circular body with diagonal flow arrow
- Gate valve: rectangle with waist
- Ball valve: circle with solid black ball symbol
- Butterfly valve: circle bisected by chord representing the disc

Consistent symbology ensures clear communication among engineering, operations, and maintenance teams.

9. Advanced Trends and Smart Valves

The integration of smart positioners, embedded diagnostics, and IIoT connectivity enables real-time valve health monitoring and adaptive control. Digital twins simulate valve performance under varying conditions, facilitating predictive maintenance and reducing unplanned downtime.

10. Maintenance and Troubleshooting

Common control valve issues include stiction, trim erosion, seat leakage, and positioner calibration drift. A predictive maintenance program employing vibration, acoustic, and position feedback can detect degradation early, optimize repair schedules, and extend valve life.

11. Conclusion

Understanding the myriad control valve types, their actuators, flow characteristics, and trim options is essential for designing robust, efficient, and safe process control systems. Advances in smart diagnostics and digital integration continue to enhance valve reliability and operational insight.

Where to buy the best Control Valves? You can choose to buy them from QTE Technologies. We, a global MRO provider, serve customers in over 180 countries. Established in 2010, we offer over 1 million products for every industry and engineering discipline. Additionally, you can reach us anytime via 24×7 chat support, phone, WhatsApp or email. Discover what our valued customers have to say about our services on our dedicated review page.

Post Author By QTE Technologies Editorial Staff (with a solid background in both technical and creative writing - accumulated 15+ years of experience).

FEATURED NEWS



How Industry 4.0 is Making a Positive Change to Industrial Manufacturing?

07/25/25

How Electronic Procurement Helps Businesses Gain a Competitive Advantage

04/21/25

Looking for investors

04/18/23

WAREHOUSE OPERATION AND MANAGEMENT WITH ROBOT & AI CREATIVE INTELLIGENCE

01/02/21

Sign up for the newsletter - the opportunity to receive promotions

Enter the email to receive news...

Sign up for the newsletter »

QTE TECHNOLOGIES CO.,LTD

Head Office

Address: 11th Floor, Zen Tower, No.12 Khuat Duy Tien St, Thanh Xuan Ward, Hanoi, Vietnam

Phone: +84 935 486 698

Hotline: +84 935 486 698

Email: info@qtetech.com.vn

Website: https://qtetech.com/

Transaction office in Ho Chi Minh City

Address: 18th Floor - Indochina Park Tower - 04 Nguyen Dinh Chieu St, Tan Dinh Ward, Ho Chi Minh City, VietNam

Phone: +84 935 486 698

Hotline: +84 935 486 698

Email: info@qtetech.com.vn

Website: https://qtetech.com/

Transaction office in Da Nang

Address: 9th Floor - Lighthouse Building - No.1254 Xo Viet Nghe Tinh - Hoa Cuong Ward - Da Nang City - Vietnam

Phone: +84 935 486 698

Hotline: +84 935 486 698

Email: info@qtetech.com.vn

Website: https://qtetech.com/

CONNECT WITH US

LINK

- About
- Catalog
- Ordering guide
- Payment guide
- Privacy Policy
- Return Policy
- Shipping Policy
- Warranty Policy
- Complaint settlement policy
- Policy with the manufacturer
- Recruitment
- Contact us
- Tax / Duty (Duties)
- Compliance/ Export Control
- Help Center/ Terms and Conditions
- FAQ